

UL633N

Applications

General Construction

- Levelling concrete forms and footers
- Single and Dual slope grading
- Vertical alignment such as anchor bolt and form alignment
- Steep slope grading
- Slope work for sports fields, tennis courts, driveways, parking garages, ramps

Interior

- Layout of walls
- Installation of drop ceilings



The Most Versatile Construction Laser, Ever



The UL633N is the unique construction laser to enable the total control of all three axes (X/Y/Z). This is accomplished via simultaneous Radio and Infrared communication and also completely new “fan beam” technology for the Z axis.

Benefiting from Spectra Precision’s know-how, the UL633N is appropriate for all applications delivering an easy, fast and accurate job.

Key Features

Total Control of X/Y Axes

- Unlimited Automatic Dual Axis Features (Simultaneously in the X- and Y- axes)
- High Precision Axis Alignments
- Simplified Grade Match: measures and displays the existing grade over unknown ground
- Complete PlaneLok: automatically locks on the laser beam to an existing elevation
- All functions flexible from 10 to 170 degrees

Total Control of Z Axis

- Automatic Detection of plumb beam
- Spot Align: aligns the plumb beam to a desired position
- Spot Match: displays the measured Z-axis grade value
- SpotLok: locks automatically the plumb beam to the SF601 center point

- Manual Detection of plumb beam
- Spot Search

Versatile Communication Links

- Radio (2 radio channels)
- IR

Built for Today’s Jobs

- Fully automatic up to +/-25% grade on X/Y/Z axes
- Withstands a 1 m (3 ft) drop onto concrete
- Long operating range - 800 m (2,600 ft) diameter
- Long operating radio range - 150 m (490 ft)
- Intuitive keypad
- Mask mode
- Includes HL760 Digital Readout Receiver
- Automatic temperature compensation
- Electronic leveling vibration filter

User Benefits

- Versatility to fit any construction application
- Quickly adapts to site requirements
- Simplifies 90° layout applications
- Reduces time to do slope work



UL633N – Construction Tough – Extremely Reliable – Easiest to Use

UL633N Specifications

- Leveling accuracy^{1,3}: ± 0.5 mm/10 m, 1/16" @ 100 ft, 10 arc seconds
- Grade accuracy^{1,3}: ± 1.0 mm/10 m, 1/8" @ 100 ft, 20 arc seconds
- Grade temperature drift sensitivity: ± 0,3 mm / 10 m / 1°C; 1/16" @ 310 ft. @ 1°F
- Operating diameter^{1,2}: appr. 800 m (2600 feet) with detector
- Grade range (Y;X): ± 25% both axes (not simultaneously)
- Grade range (Z): ± 25%
- Rotation: 0 - 750 rpm
- Scan mode: 5 preset sizes + variable adjustment
- Laser type: red diode laser 650 nm
- Laser class : Class 3
- Self-leveling range: appr. ± 14°
- Leveling indicators: LCD indications and LED flashes
- Radio range (HL760)^{1,2,4}: up to 150 m (490 ft)
- Power source: NiMH battery pack/alkalines
- Battery life¹: 35 hours NiMH
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Storage temp.: -20°C to 70°C (-4°F to 158°F):
- Tripod attachments: 5/8 x 11 horizontally and vertically
- Dust and waterproof: Yes - IP67
- Weight: 3.1 kg (6.8 lbs)
- Low voltage indication: LCD battery indicator
- Low voltage disconnection: unit shuts off
- Warranty: 5 Years

HL760 Digital Readout Receiver

- Highly versatile receiver for basic and advanced leveling and aligning applications
- Works with UL633N in automatic Axis Alignment, Grade Match and PlaneLok applications
- Key Features:
 - Digital readout of elevation
 - Exact distance from grade displayed
 - Anti-strobe sensor to prevent false reading from jobsite strobe lights
 - Large reception height to ease beam reception
 - Withstands a drop of up to 3m (10ft)
 - Radio communication - works with another HL760 for long range wireless remote display and monitoring capability
- User Benefits:
 - No need to go "on-grade" to measure;
 - Saves considerable time
 - Reduces rework by allowing remote monitoring
 - Increases reliability, accuracy and durability

RC603N Remote Control Specifications

- Operating range^{1,2,4}: up to 150 m (490 ft)
- Power source: 2 x 1.5V AA alkaline batteries
- Battery life¹: 130 hours
- Dust and waterproof: Yes - IP66
- Weight: 0.26 kg (0.57 lbs)

Spot Finder SF601 Specifications

- Operating range^{1,2,4}: up to 80 m (260 ft)
- Power source: 4 x 1.5V AA alkaline batteries
- Battery life¹: 30 hours
- Dust and waterproof: Yes - IP67
- Weight: 0.43 kg (0.95 lbs)

HL760 Digital Readout Receiver Specifications

- Digital readout units: mm, cm, ft, in, frac. in
- Reception height: 127 mm (5 inches)
- Six On-grade sensitivities:
 - Ultra Fine 0.5 mm (~1/32 in)
 - Super Fine 1 mm (~1/16 in)
 - Fine 2 mm (~1/8 in)
 - Medium 5 mm (~1/4 in)
 - Coarse 10 mm (~1/2 in)
 - Calibration Mode 0.1 mm (~1/64 in)
- Battery life (2 x AA): 60+ hours continuous operation
- Auto shut-off: 30 minutes/24 hours
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Drop performance: 3 m (10 ft)
- Dust and waterproof: Yes - IP67
- Weight: 0.27 kg (9.5 oz)
- Warranty: 3 Years "No Excuses"

⁽¹⁾ at 21° Celsius (70° F)

⁽²⁾ under optimal atmospheric circumstances

⁽³⁾ along the axis

⁽⁴⁾ Height of instruments typ. 1m (e.g. with tripod)



RC603N Combined Radio/IR Remote Control for all applications



HL760 Digital Readout Receiver to measure and display beam location



SF601 Spot Finder for manual and automatic detection of the plumb beam

